RFID Chips Are Here What You Need to Know

Washington University in St. Louis

R. Scott Granneman

© 2013 R. Scott Granneman
Last updated 20131116
You are free to use this work, with certain restrictions.
For full licensing information, please see the last slide/page.

Fake Links

Need to create a fake link?

Easy

Fake link

<d1v> inside <div> Don't be afraid to nest
<aiv inside </aiv>
(or other block-level elements either)

```
<div id="page-container">
  <header>
    Header content
  </header>
  <div id="main-container">
    Main content
  </div>
  <aside>
    Aside content
  </aside>
  <footer>
    Footer content
  </footer>
</div>
```

Pseudo Classes

- is always a paragraph
- <hr> is always a horizontal rule</hr>
- is always emphasized text

These elements are always in the same *state*

<a>> can be in 4 different states

Link
Visited
Hover
Active

a:link

A link on a webpage, unvisited or clicked on

What does it look like by default?

Blue Underlined Cursor is an arrow

a:visited

A link on a webpage after you've clicked on it & visited it

What does it look like by default?

Purple
Underlined
Cursor is an arrow

a:hover

A link on a webpage as you hover your cursor over it

What does it look like by default?

Blue (or purple)
Underlined
Cursor is a hand

a:active

A link on a webpage at the moment you click on it

What does it look like by default?

Red (IE, a long time ago)
Underlined
Cursor is a hand

You may need to differentiate between different uses of <a>

```
<div id="page-container">
  >
    Lorem ipsum <a href="//
chainsawonatireswing.com">dolor sit
amet</a>.
 </div>
<footer>
  © 2013 <a href="//
www.granneman.com">Scott
Granneman</a>
</footer>
```

```
#page-container a:link,
#page-container a:visited,
#page-container a:hover,
#page-container a:active {
  color: #800000;
  text-decoration: none;
footer a:link,
footer a:visited,
footer a:hover,
footer a:active {
  font-family: Helvetica, sans-serif;
  border: 1px dotted #e9e9e9;
```

If necessary, you can always attach a class to an a

a.class:visited {...}

Side Note

By the way, there are other pseudo-classes, including

- :first-letter
 - :first-line
 - :first-child

HTML5 Elements



<hgroup> is dead

Mozilla Developer Network: "This element has been removed from the HTML5 (W3C) specification"

<hgroup>

"... used to group a set of h1-h6 elements when the heading has multiple levels, such as subheadings, alternative titles, or taglines."

http://www.w3.org/TR/html5/semantics.html#the-hgroup-element

```
<hpre><hgroup>
     <h1>
          Google Apps Deciphered
      </h1>
        <h2>
          Compute in the Cloud
        </h2>
</hgroup>
```

<footer>

Replaces <div id="footer">

<footer> is not just for pages,
 but also for <section> too

Info such as:
 author
 copyright
links to related content
 contact info

Thank you!

scott@granneman.com

www.granneman.com

ChainSawOnATireSwing.com

@scottgranneman

RFID Chips Are Here What You Need to Know

Washington University in St. Louis

R. Scott Granneman

© 2013 R. Scott Granneman

Last updated 20131116

You are free to use this work, with certain restrictions.

For full licensing information, please see the last slide/page.

Licensing of this work

This work is licensed under the Creative Commons Attribution-ShareAlike 3.0 Unported License.

To view a copy of this license, visit http://creativecommons.org/licenses/by-sa/3.0/deed.en_US

In addition to the rights and restrictions common to all Creative Commons licenses, the Attribution-ShareAlike License features the following key conditions:

Attribution. The licensor permits others to copy, distribute, display, and perform the work. In return, licensees must give the original author credit:

Scott Granneman • www.granneman.com • scott@granneman.com

Share Alike. The licensor permits others to distribute derivative works under a license identical to the one that governs the licensor's work.

Questions? Email scott@granneman.com